

## JAINAM

MULTI-PRODUCT(INDIA)PYT.LTD





Allow the location to be pinpointed accurately and rapidly

Ip65 dust and water proof

Water-resistant design ensures stable operation in tough environment

Two-way talk

With MIC and speaker connected, it's easy to realize two-way audio

Voice monitor

Activate voice-monitoring mode via text

SIM change alarm

If anybody change the SIM card, alert will be sent

SOS call

Thumb sized button allowing urgent call during an emergency case

Recording

Send SMS command to record and the audio file will be uploaded to the platform

6 days standby

In power saving mode, the battery can last 6 days

## **G**sm specifications

GSM frequency	GSM 900/1800MHz
GPRS	Class 12, TCP/IP
Memory	32+32Mb
Phase error	RMSPE<5,PPE<20
Max output	GSM850/GSM900:33±3dBm, GSM1800/GSM1900:30±3dBm
Max frequency error	±0.1ppm
Receive sensitivity	Class II RBER2%(-106dBm)

## **G**ps specifications

GPS chipset	High sensitivity chip
Frequency	L1,1575.42MHz C/A code
GPS channel	66
Location accuracy	<10 meters
Tracking sensitivity	-165dBm
Acquisition sensitivity	-148dBm
TTFF (open sky)	Avg. hot start ≤1secAvg. cold start ≤35sec

## Function & package

Voice monitor range	≤ 5meters
Button	1xSOS, 1xPower On/Off
GSM/GPS antenna	Built-in quad band GSM antenna, GPS ceramic antenna
Working time	6 days (Wi-Fi positioning, location data uploaded at 10 minutes interval)
Operating temperature	- <b>20</b> °C ~70°C
Device weight	70g
Device dimension	69.0 x 41.0x 16.0mm
Waterproof grade	Ip65
LED	Status LED
Battery	900mAh/3.8V
Charger	5VDC/1A

Add.: 509, 5th Floor, Fortune Square-II, Daman Road, Landmark TBZ, Chala, Vapi - 396191, Gujarat.

98252 49766 | 98257 49766 | 89800 17818

 Ahemdabad
 |
 Bangalore
 |
 Chennai
 |
 Daman
 |
 Mumbai
 |
 Nagpur

 7069034346
 76195 63284
 8980014344
 9724375577
 7069034348
 9561111233