

JAINAM M



GT06E 3G GPS Multifunctional Tracker

- Remote cut-off (petrol/power)
 Compel the vehicle to stop by breaking off the fuel connection
- ACC detection for ignition status
 Be aware of the ignition status
 whenever you need
- Configurable tracking modes
 Location uploaded following fixed
 distance, time interval, preset cornering
- Multiple analog & digital I/O
 Monitor and control external
 application via input/outputs

- WCDMA & GSM
 Use 3G network (outstanding coverage, no 2G worries)
- SOS emergency call
 Thumb sized button allowing urgent call during an emergency case
- Multiple alarms
 Instant alert for vibration, overspeed,
 power off, geo-fence
- Tracked by: SMS, APP, Web
 Report location in real time through
 different interfaces

Application



Gsm specifications

GSM frequency	850/900/1800/1900 MHz
GPRS	Class 12, TCP/IP
Memory	32+32Mb
Phase error	RMSPE<5,PPE<20
Max output	GSM850/GSM900:33±3dBm, GSM1800/GSM1900:30±3dBm
Max frequency error	±0.1ppm

Gps specifications

GPS chipset	MTK high sensitivity chip
Frequency	L1,1575.42MHz C/A code
GPS channel	66
Location accuracy	<10 meters
Tracking sensitivity	-162dBm
Acquisition sensitivity	-148dBm
TTFF (open sky)	Avg. hot start ≤1secAvg. cold start ≤35sec

Function & package

Battery	270mAh/3.7V Li-Polymer battery
Working voltage/current	9-90VDC/7mA(60VDC)
Standby time	60 hours
Working time	3 hours
Operating temperature	-20°C ~70°C
Device weight	41g
Device dimension	81.0(L)*43.0(W)*10.0(H)mm

Add.: 509, 5th Floor, Fortune Square-II, Daman Road, Landmark TBZ, Chala, Vapi - 396191, Gujarat.

98252 49766 | 98257 49766 | 89800 17818

 Ahemdabad
 |
 Bangalore
 |
 Chennai
 |
 Daman
 |
 Mumbai
 |
 Nagpur

 7069034346
 76195 63284
 8980014344
 9724375577
 7069034348
 9561111233