



X3

Multifunctional Vehicle Tracker

- | | |
|--|---|
| <p>➤ GPS+LBS positioning
Allow the location to be pinpointed in real time or periodically</p> | <p>➤ Rs232 & TTL
Support fuel level sensor, temperature sensor, RFID, etc</p> |
| <p>➤ Two-way talk
MIC and speaker for two-way audio With MIC and speaker connected, it's easy to realize voice-monitor or two-way audio</p> | <p>➤ Multiple I/Os
Monitor and control external devices</p> |
| <p>➤ Remote cut-off (petrol/power)
Compel the vehicle to stop by cutoff the fuel connection</p> | <p>➤ Door status detection
Get instant alert when car's door is opened unexpectedly</p> |
| <p>➤ Heat-resistant design
Get instant alert when car's door is opened unexpectedly</p> | <p>➤ Multiple alarms
Multiple Instant alert for vibration, overspeed, power off, geo-fence</p> |

Application



Fleet Management



Vehicle tracking



Taxi

Gsm specifications

GSM frequency	850/900/1800/1900 MHz
GPRS	Class 12, TCP/IP
Memory	32+32Mb
Phase error	RMSPE<5,PPE<20
Max output	GSM850/GSM900:33±3dBm GSM1800/GSM1900:30±3Bm
Max frequency error	±0.1ppm

Gps specifications

GPS chipset	MTK high sensitivity GPS chip
Frequency	L1,1575.42MHz C/A code
GPS channel	Built-in, 25*25*4mm
Location accuracy	<10 meters
Tracking sensitivity	-162dBm
Acquisition sensitivity	-148dBm
TTFF (open sky)	Avg. hot start≤1sec, Avg. cold start≤35sec

Function & package

Voice monitor range	≤5meters
Battery	450mAh/3.7V Li-Poiymer battery
Working voltage/current	9-36VDC/45mA(12VDC), 28mA(24VDC)
Standby current	≤5mA
Operating temperature	-20 ~ 70
Dimension	80(L) ×55.8.0 (W) ×23.4 (H) mm
Weight	95g

Add.:509, 5th Floor, Fortune Square-II, Daman Road, Landmark TBZ, Chala, Vapi - 396191, Gujarat.

 98252 49766 | 98257 49766 | 89800 17818

Ahemdabad | **B**angalore | **C**hennai | **D**aman | **M**umbai | **N**agpur
7069034346 | 76195 63284 | 8980014344 | 9724375577 | 7069034348 | 9561111233